

“EVO” EXPANDING ADJUSTER FOR THREADLESS FORKS

FIRST WARNING

These instructions are for the “EVO” expanding adjuster only. Because an improperly installed, bicycle fork can lead to loss of control, injury, and death, if you have not previously installed a threadless fork, take your bike to a qualified mechanic

SECOND WARNING

Before inserting the adjuster, make sure the stem extends 2 – 5mm above the top of the fork steerer. If you do not understand this instruction and/or are uncertain as to how a threadless headset is installed and adjusted, a professional bicycle mechanic can check the fork and headset installation before demonstrating the proper adjustment sequence.

THIRD WARNING

Do not overtighten. The “EVO” expanding adjuster adjusts headset tolerance. It does not fasten the fork to the frame.

NOTICE TO MECHANICS

Installation of the “EVO” expanding adjuster is simple enough to confuse an experienced mechanic. Those who think this unit “looks wrong” have made the mistake of inverting the expander tube. The slotted end of the expander tube must face upward – honest!

INSTRUCTIONS

1. There is no need to disassemble the unit.
2. Twist the ribbed expander tube onto the bolt, until the entire unit is a press fit into the fork steerer.
3. Tighten or loosen the bolt to achieve proper headset adjustment.
4. Lock the adjustment by tightening the stem onto the fork.

Problems? the correct assembly order for the unit (top to bottom) is as follows:

Allen bolt (head faces up)
Alloy “EVO” cap (lettering faces up)
Steel washer with outside diameter same as spring’s
Steel spring
Steel washer with outside diameter same as spring’s
Thick alloy washer (recess for small washer faces up)
Slotted and ribbed expander tube (SLOTTED END MUST BE UP)
Threaded expander plug (nipple faces down)



FOR CUSTOMER SERVICE PLEASE PHONE: 1 (909) 596-7570 x72